

Verlegeanleitung CASALoc



Rev. 7.1 / 01.21

1 rel. hum. 40-60%
temp. >18°C/64°F (48 h)
≥ 30 cm
12 in

2 CA 0,3 CM % CT 1,8 CM %
max. 2 mm / 1 m
1/4 in / 3 ft

3 max. 3 mm, 1/8 in
0,2 mm PE

4 2 cm
2 1/2 in
20 cm
7 7/8 in

5 x=10 mm
3/8 in

6 max. 29°C
84°F

7 rel. hum. 40-60%
temp. >18°C/64°F

8 > 8 cm
3 1/8 in

9 > 8 cm
3 1/8 in

10 x=10 mm
3/8 in

11 11 m
36 ft

12 11 m
36 ft

13 11 m
36 ft

14 x=10 mm
3/8 in

15 x=10 mm
3/8 in

16 A
B
1
2
3
∠ 20-30°

17 1
2
3

18 3
2
1

19 1
2
3

20 3
2
1

21 1
2
3

22 3
2
1

23 ø+20 mm
3/4 in

24 ø+20 mm
3/4 in

25 V1 > 8 cm
3 1/8 in

26 V1 10 mm
3/8 in

27 V1 ø+20 mm
3/4 in

25 V2 10 mm
3/8 in

26 V2 +10 mm
3/8 in

27 V2 > 8 cm
3 1/8 in

28 Office chair

29 Chair and table

30 Vacuum cleaner

31 Bucket and mop

32 Final floor view

33 1
2
3